21

**RJ-250SC** Self-Contained Compactor

RJ-250SC 34 cu. yd. configuration pictured

### **RJ-250SC Features**

- Great for waste with high liquid content
- ▼ Qwik Clean® Tank
- ▼ Full Door Seal With P-Seal
- ▼ CYCON Life-Xtender<sup>™</sup> Cyclic Control System
- Customizable For Your Application

### **The Worldwide Compaction Leader**

Marathon<sup>®</sup> Equipment is known throughout the world as one of the leading manufacturers of quality on-site waste compaction products. The RamJet<sup>®</sup> brand has been the industry standard for quality and innovation for more than 50 years, and includes stationary and self-contained compactors, compaction containers, apartment, and high-rise compactors, pre-crushers, auger-style compactors, transfer systems, and a wide array of options for virtually any application.





MARATH

1 1

R




### **RJ-250SC Compactor**

MARATHON ®

Overview

#### Perfect for:



### Why Marathon® Equipment Is the Preferred Choice

**Marathon** components are selected for longevity and minimum maintenance, with special attention given to the selection of high-duty cycle components. Stress engineering provides the optimum degree of structural integrity. Only the best materials are used, and the highest standards of quality are observed in the manufacturing process.

Our RamJet<sup>®</sup> units are state-of-the-art in roll-off self-contained compactors, featuring large feed openings, and expanded container storage capacity. They are designed to optimize safety for workers, store and transport your waste, prevent contamination of public areas in accordance with public health department requirements, improve working conditions for your employees, and reduce disposal costs.

The RJ-250SC compactor can be customized with a variety of loading arrangements to suit your specific needs.

The RJ-250SC is perfect for weekly volumes of more than 100 cubic yards of wet or general waste materials. All models have a packer head permanently attached to the container.

Some images shown with optional equipment



### **RJ-250SC Series Compactor**



**Features** 



### **RJ-250SC Features**

- Exclusive 41" x 58" feed opening to handle large, bulky items
- Continuous feeding capability even while the compactor is operating
- Adaptable to special loading systems such as large-capacity hoppers, security chutes, or total enclosures
- Odor and pest control from the Marathon<sup>®</sup> Ozone Odor Control option
- Easy loading from either ground or dock level
- Up to 24 tons of crushing force to reduce refuse to a fraction of its former size, saving valuable space and reducing landfill trips
- Fire hose connection provided on each unit
- Factory testing to ensure leak-proof construction



#### Perfect for Tipper System Applications

The RJ-250SC is the perfect choice for applications requiring a tipper system. These tippers can extend the benefits of compaction to all areas of your operation while keeping equipment investments to a minimum. Carts or containers can be located at individual waste generation sites within the operation, and then emptied into the compactor with the cart tipper option.

Some applications require a high degree of security and sanitation. The RJ-250SC provides both. Waste is safely stored out of reach of scavengers. Sanitary conditions are enhanced even further with the optional **Marathon** Ozone Odor-Control System, which destroys odorproducing bacteria by molecular reaction.



#### Available with Bayne Thinline® Cart Lifter

If equipped with an optional integral cart lifter, the RJ-250SC offers an economical and safetyconscious solution for a wide variety of waste material handling applications.

Bayne Thinline<sup>®</sup> cart lifters work with standard two-bar roll-out carts and can lift up to 750 lbs. They feature a durable, powder-coated finish, which provides protection from the elements, and allows for easy cleaning.



### **RJ-250SC Series Compactor**

The perfect compactor for high-volume wet waste

RARATHON ®


- V Large 41" x 58" Feed Opening
- Full Door Seal with P-Seal
- Bubble Gate with Auto Relatch and Double-Hinge Door
- Qwik Clean® Tank
- ▼ Cycon Life-Xtender<sup>™</sup> Cyclic Control

#### **P-Seal Watertight Closure**

The P-shaped Door Seal is specially designed for portable compaction containers, providing a superior, watertight closure. The mounting is engineered for quick and easy installation when replacement is necessary, requiring no field fitting, cutting, or welding.

# Double-Hinge with Bronze Bushing

Every RJ-250SC is tested for water-tightness before leaving the factory. Liquid retention is ensured by the incredible Double-Hinge. It creates uniform seal compression while eliminating the seal "scrubbing" and damage often encountered with competitive designs. The Double-Hinge also saves expensive driver and truck time as only one easy-to-operate ratchet is required to make it work.



The innovative "Bubble Gate" adds a full cubic yard to container

capacity. Superior compaction ratios result from its special curved

shape. These two unique benefits reduce costs of disposal.

#### **Auto Relatch**

The ultimate in latch systems, the Marathon<sup>®</sup> "Auto Relatch" eliminates the need to hold the door while operating the latch ratchet. This design enables the operator to use both hands on the ratchet.



#### **Ram Guide System**

The packing ram is supported by specially formulated cast-iron shoes, which ride on replaceable wear strips. This exclusive design protects the charge-box floor from the full force of the packing ram, extending its life, and dramatically reducing compaction-robbing friction.



**Bubble Gate and Auto Relatch** 

### **RJ-250SC Series Compactor**

**Features** 




### **Remote Power Pack**

Separate from the compactor/container, the Marathon<sup>®</sup> Remote Power Pack remains free of damage caused while hauling to and from disposal sites, and stays free of problems caused by landfill dust. There are no electrical connections to make or break, and two simple-to-use, hydraulic quick disconnects couple the power unit to the packing head. All **Marathon** Remote Power Packs are built in-house to our quality standards, and each unit must pass a series of stringent tests before it can be shipped with the selected compactor.



#### **Optional Doghouse**

The optional doghouse offers a totally enclosed charge box with heavy-duty latches.



#### **Qwik Clean® Tank Feature**

The **Qwik Clean** Tank feature, standard on all RJ-250SC compactors, funnels any liquid seepage, which can occur during compaction, into an enclosed area underneath the charge-box floor. Liquid is automatically discharged at the disposal site, in effect flushing the container and the area behind the ram. The 12" high, up to 750-gallon capacity sump area is designed to provide easier hook access for roll-off drivers.



MARAT

### Cycon Life-Xtender™ Cyclic Control System


# Standard on all RJ-250SC and RJ-250SC Ultra Compactors

- Reliable, solid-state circuitry eliminates all pressure and limit switches
- The Cycon Life-Xtender noshock cycle control extends cylinder and hose wear life
- Automatic "container full assurance system" — the ram dwells against the load at full pressure, resulting in better compaction
- Smoother running, quieter operation
- Advanced hydraulic design enables the system to operate at minimum pressure levels until the need for more pressure is automatically sensed
- More accurate Advanced Warning or Container Full options
- Dramatically improved coldweather performance



### **RJ-250SC Series Compactor**

**Features** 



#### StreamLine® Option

The **StreamLine** option enables excess liquid to be drained from the container, reducing net payload weight, and significantly reducing hauling costs. Liquid is routed to four interconnected 4" drain outlets, located at each corner of the **StreamLine** unit. Connection can be made to a hose, piping, or a pump.



#### **Qwik Clean® Door**

The **Qwik Clean** door on the packer end makes cleaning out behind the ram-incylinder area a snap. The door has miniature hinges, a door seal, and a ratchet binder. Also, featured is the RamJet<sup>®</sup> rear-feed-doghouse door option.





#### **Compactor Fundamentals**

1

3

4

5

6

7

?

*Eight simple items to consider when choosing the perfect compactor for your application:* 

- Recyclables Is there sufficient volume of recyclable materials to warrant more than one compaction system or is recycling mandatory?
- 2 Size of Waste Is the Feed (Clear Top) Opening large enough to accommodate the largest items without bridging?
  - Safety Standards Does the installation comply with recommended ANSI standards? Is there an access interlock switch on chute or hopper doors and gates? Is a "momentary contact" control required?
  - **Power Source** Is adequate power available? Three or single phase?
  - **Convenience** Is the compactor located for easiest use? Loading height? Can a hopper, doghouse, (charge box enclosure) or cart dumping system improve convenience? Can value be added (building or employee security) by loading through the wall? Would an Ozone Odor Control System solve odor or pest control problems?
  - Volume of Waste Generated Will the compactor be adequate to handle the volume generated during the peak load periods?
  - ) Location Does, or can, the waste flow to one central point?
- 8 Available Space Is there space for the Compaction System and maneuvering room for collection trucks? Is there adequate overhead clearance? Is there compatibility with the collection truck?
  - Have Questions? If you have any questions or need assistance with your compaction needs, please call **1-800-633-8974** and speak to a specialist. We are here to help!



# RJ-250SC & RJ-250SC Ultra

120 VAC

2-Push Button Station

Start/Stop

**Dimensions & Specifications** 

Specifications		<b>B</b>   05000					_	Classic	Ultra	
Clear-Top Opening (L x W)	41" x 58"	1041mm x 1473mm	RJ-250SC	A	B	C	D	E	Weight	Weight
Compactor Capacity	1.31 yd <sup>3</sup>	1.00 m <sup>3</sup>	15 Cu. Yd.	48"	43 ¼"	67"	171"	89"	8,860 lbs.	8,360 lbs.
Ram-Face Size (W x H)	60" x 24 <sup>1</sup> /2"	1524mm x 622mm		1219mm	1099mm	1702mm	4343mm	2261mm	4019 kg	3792 kg
Performance Characteristics			20 Cu. Yd.	48"	43 ¼"	67"	208"	89"	9,520 lbs.	8,860 lbs.
• · •			20 Gu. fu.	1219mm	1099mm	1702mm	5283mm	2261mm	4318 kg	4019 kg
Cycle Time		33 sec.			43 ¼"	67"	214"	104"	10,030 lbs.	9,720 lbs.
Total Normal Force	39,900 lbs.	177 kN	25 Cu. Yd.	1219mm	1099mm	1702mm	5436mm	2642mm	4550 kg	4205 kg
Total Maximum Force	49,500 lbs.	220 kN	30 Cu. Yd.	48"	43 ¼"	67"	245"	104"	10,620 lbs.	9,715 lbs.
Normal Ram-Face Pressure	27.1 psi	187 kPa		1219mm	1099mm	1702mm	6223mm	2642mm	4817 kg	4407 kg
Maximum Ram-Face Pressure	33.7 psi	232 kPa	34 Cu. Yd.	48"	43 ¼"	67"	269"	104"	11,130 lbs.	10,100 lbs.
	•			1219mm	1099mm	1702mm	6833mm	2642mm	5049 kg	4582 kg
Ram Penetration	6"	152mm		48"	43 ¼"	67"	299 1⁄2"	104"	11,790 lbs.	N/A
Electrical Equipment			39 Cu. Yd.	1219mm	1099mm	1702mm	7607mm	2642mm	5348 kg	N/A
Electric Motor 3/60/230-460	10 hp	7.5 kW	Pictures and mechanical diagrams in this literature are illustrative only and may not be to scale. Specifications are							

Pictures and mechanical diagrams in this literature are illustrative only and may not be to scale. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Certified in compliance with ANSI standard Z245.2, all applicable OSHA Regulations. Products must be used only by trained operators in accordance with the Operator Manual, as well as applicable regulations, laws, and ANSI standards

lydrau		Ean	nmont
ivul du	116	EUUI	UIIEIL

**Standard Controls Include** 


**Electric Control Voltage** 

9 gpm	38 L/min						
1,850 psi	128 bar						
2,300 psi	159 bar						
2							
4"	102mm						
2 <sup>1</sup> / <sub>2</sub> "	64mm						
31 1/2"	800mm						
	1,850 psi 2,300 psi 4" 2 1/2"						

RJ-250SC Classic containers are constructed out of 7-gauge steel plate. RJ-250SC Ultra containers are constructed out of 11-gauge steel.

#### We're Here To Help!

For detailed specifications, recommendations, or to request a site survey comparing various systems, contact the Marathon® Sales Team at MarathonSales@MarathonEquipment.com



Dimensions not shown: 100 1/8" (2543mm) Overall Width

Ground Roller Widths: 61 1/8" (1572mm) Inside Rollers  $67 \frac{3}{8}$ " (1711mm) Roller Centers 72  $\frac{7}{8}$ " (1851mm) Outside Rollers

**Authorized Dealer:** 









Awarded Contract

Contract # 040621-MEC

Marathon Equipment Company P.O. Box 1798 Vernon, AL 35592-1798

Learn more about Marathon Equipment: 800.633.8974 | www.marathonequipment.com